

Definition

ISOFIX PLUS is an aqueous formulation containing acrylic polymers in suspension. This organic adhesive has been developed to fix spray-applied rock wool with inorganic binders, on all surfaces that are either delicate or difficult to treat with the usual methods.

Uses

ISOFIX PLUS is especially recommended for ensuring the adhesion of the fibrous mixes ISOTHERM and/or ISOFLAM and/or ISOFLAM SM on a variety of difficult surfaces such as extremely smooth or porous surfaces.

Características

Colour	Milky white
State	Viscous liquid
Brookfield viscosity	10000 – 12000 cP at 22°C
Coverage	300 to 400 g/m ² (depending on the application)

Application

- Product ready for use, does not require dilution
- Application: with a roller, max. 20 min. (depending on the climatic conditions) before applying the blown product (the adhesive must still be tacky).
- On a dry, clean and undamaged surface, following removal of any traces of stripping products, laitance, flakes or paint residues.
- The ambient temperature and the temperature of the surface must be greater than +5°C.

Precautions for use

- Use of gloves and goggles recommended
- In case of accidental projection into eyes, flush eyes with abundant water for 5 min. If an irritation develops, consult a physician.
- In case of contact with skin, wash the part affected with water and soap.
- In case of accidental ingestion, drink water but do not induce vomiting.

Packaging / Storage

- Packaging: in 30 kg polyethylene drums.
- Storage: approx. 6 months between 6°C and 35°C in the original packaging hermetically sealed.